

WEATHER PROOF PREMIUM ANTI DUST

DESCRIPTION

“ANTI-DUST” special acrylic is a premium quality paint that is extensively efficacious for exterior walls. It is exclusively weather-friendly. It resists dirt, fungus oozing water from the wall, and emission of detrimental gases of the biosphere along with protecting the wall during scorching heat or excessive rainfall. The paint is a paramount quality colorant. As it is made from nano additives technology, it resists the ultraviolet rays of the sun that don't let the color become pale. Therefore, the exterior wall remains glistening over the years.

FEATURES AND BENEFITS

- Excellent water-resistant property
- Highly durable
- Resistance properties against fungi, algae and dampness caused by lashing rain
- Available pleasing shades

USES

All exterior walls, Cement plaster, concrete stone, brick, asbestos and all types of building boards.

TECHNICAL SPECIFICATION

Binder	: Pure acrylic Emulsion
Pigmentation	: Titanium Dioxide and Mineral extenders
Colorant	: Universal colorant
Solvent	: Water
Solid by weight	: 53%
Viscosity	: (6-7) thousand mPa.s
Sp. Gravity	: 1.25 – 1.30
Coverage	: 170-180 Square feet /Ltr/Coat (Depend on Surface)
Flammability	: Not applicable

Touch dry	: 30 minutes (At 30°C)
Hard dry	: 24 hours (recoat)
Clean up solvent	: Water
Thinner	: Clean Water
Sheen 600 Value	: Egg Shell
Shade / Color	: As per Moon star Shade card, Color choice shade card and any customized shade

SURFACE PREPARATION

The surfaces must be clean, dry, and free from dirt, oily substance, fungus, saltiness and corrosion as well as old painted substances. For new walls make sure of perfect dryness. Then scrub well with stone. Next, make sure it is moisture free. Apply one coat of Moon Star weather proof sealer after dryness. After 6-8 hours, when the sealer gets dried observe the surface condition. Then apply Moon Star wall care putty if needed. Apply Moon Star Salt Sealer if the wall is salty. Apply another coat of sealer after 24 hours of finishing with sandpaper in order to prepare a suitable surface.

APPLICATION METHODS

Stir well after opening the container. It can be applied with a brush, roller or spray.

THINNING METHOD

For Brush Paint : Water = 2 : 1 (By volume)

For Roller Paint : Water = 3 : 1 (By volume)

Quality may not be ensured if diluted excessively. Two coats are enough for final finishing. Apply the next coat after 6 hours. Apply the water-mixed paint as soon as possible and rinse the materials used.

PACK SIZE

18.2 liters

3.64 liters

PRECAUTIONS

- Keep away from children.
- If splashes enter the eyes, wash them with plenty of water.
- Emulsion-based material, should be protected from frost, heat or sunlight.
- It is non-flammable under normal conditions of use.
- Ensure good ventilation during application and drying.
- Prolonged skin contact should be avoided.

DISCLAIMER

The information given herein is based on our present knowledge and is believed to be reliable. We can't assume any responsibility since the usage conditions are beyond our control.